

Monitored PDU (Local)

Installation configurations:

The 19" - 1U PDU's designed for installation in server and cabling racks



Power & Temperature:

Operating voltage: 250VAC 50VHz
Maximum current: 16A/32A
Work Temperature: up to 70°C

Local Meter:

Integrated module within the unit that gives an indication of the input voltage level and power consumption



Testing: 100% testing
continuity, polarity, insulation & earth
Certification: SII test certification
Warranty: 3 years Warranty
Packing: each item in a box

EP32A24ILMD EP32AMIXILMD EPMIXILMD EP32AI2ILMD EPIOC13MD EP6ILMD EP8ILD * Pictures for illustration purposes only

Catalog No	Model	Output receptacles	Input plug type	Cord Type	Cord length	Protection ABB	Product length
0727363258236	EP6ILMD	6 x IL 	IL	3X1.5mm ²	3M	MCB	444mm
0727363258991	EP6ILMD	6 x IL 	CEE	3X2.5mm ²	5M	MCB	444mm
0727363258243	EP8ILD	8 x IL 	IL	3X1.5mm ²	3M	—	444mm
0727363258281	EPIOC13MD	10x C13 	CEE	3X2.5mm ²	5M	MCB	444mm
0727363258274	EP6C19MD	6x C19 	CEE	3X2.5mm ²	5M	MCB	444mm
0727363259103	EPI2C13MD	12x C13 	CEE	3X2.5mm ²	3M	MCB	494mm
0727363258250	EPI2ILMD	12 x IL 	IL	3X1.5mm ²	5M	MCB	702mm
0727363259004	EPI2ILMD	12 x IL 	CEE	3X2.5mm ²	5M	MCB	702mm
0727363258304	EPI2C134C19MD	12xC13  + 4xC19 	CEE	3X2.5mm ²	5M	MCB	652mm
0727363258298	EP24ILMD	24 x IL 	CEE	3X2.5mm ²	5M	MCB	1218mm
0727363258342	EPMIXILMD	20xC13  + 4xC19  + 4xIL 	CEE	3X4mm ²	5M	MCB	1102mm
0727363258366	EP32AI2ILMD	12 x IL 	CEE 3x32A	3X6mm ²	5M	MCB	862mm
0727363258373	EP32A24ILMD	24 x IL 	CEE 3x32A	3X6mm ²	5M	MCB	1387mm
0727363258359	EP32AMIXILMD	20xC13  + 4xC19  + 6xIL 	CEE 3x32A	3X6mm ²	5M	MCB	1282mm